

SOLID MASONRY SAWS FOR UNIVERSAL CONSTRUCTION JOB SITE USE

- The water spraying system ensures optimum saw blade cooling and the immediate removal of the sawing debris with the lowest water consumption and also complies with the current safety standard
- Table saw with swivelling cutting head
- High-quality, low-maintenance construction
- Welded steel construction and plastic water basin with precise table support for accurate cuts
- The adjustable saw head also allows chop cuts
- Foldable legs for fast and compact transport
- Standard wheelset makes it easier to move on site and to load into a vehicle
- Roller table equipped with safety catch and locking mechanism
- Integrated water pump transport lock
- Removable splash guard
- Rear sloping and removable water pan
- Rubberised saw table for non-slip cuts
- Best transport option by using (back/front) handles
- Smooth cutting table with adjustable angle stop
- Hinged saw blade guard for easier exchange of saw blades
- ON / OFF switch with EMERGENCY STOP user-friendly in a protected position



| TECHNICAL DATA | DTS 402 |
|---------------------------------|------------------|
| cutting depth standard/max. | 110 mm / 135 mm |
| cutting depth standard/max. 45° | 80 mm / 105 mm |
| cutting length | 800 mm |
| saw blade Ø standard/max. | 350 mm / 400 mm |
| arbor size | 25,4 mm |
| output power max. | 2.2 kW |
| voltage | 230 V / 50 Hz |
| saw blade speed | 2800 1/min. |
| protection class | IP 54 |
| mitre cuts | 45° |
| dimensions (L/W/H) | 1200/750/1330 mm |
| weight | 84 kg |



Foldable legs



Wheelset included



Adjustable saw head

MASONRY SAWS

NR.

DTS 402 without diamond blade

1059422

ACCESSORIES

NR.

Adapter cable 2m plug Schuko | coupl. CEE 3-pin 16 A

822312

Adapter cable 2m plug CEE 3-pin 16 A | coupl. Schuko

822310

TOOL RECOMMENDATION

Concrete, Natural stone



TL BETON

Natural stone



GSWD 10